

Boundary dimensions for fabric with thickness below 0,35 mm					Boundary dimensions for fabric with thickness over 0,35 mm					System colours			
Controls	MIN	MAX	M X X	m ²	Controls	MIN	MAX	M X X	m ²	(P)	(K)	(U)	
Chain	50	280	300	6,0	Chain	50	280	250	4,5	white	black	grey	anthracite
Chain (Loopless)	50	280	300	3,0	Chain (Loopless)	50	280	250	3,0	white	anodized		
Motor DC ∅38/∅42*/∅50*	46	220/280*	300	6,5/9,0*	Motor DC ∅38/∅42*/∅50*	46	200/280*	250	5,0/7,0*		stainless steel		
Motor AC	54	280	300	9,0	Motor AC	54	280	250	7,0				


Tube ∅50 > 200 cm width

Tube ∅50 > 200 cm width

* only Coulisse CM-05, Torro AM35EB RF

Price in the table includes blind with chain control, installation profile in one of colours (P) with bottom bar type D3 or D4, mechanism and bracket covers are plastic.

The recommended maximum width for duolight roller blinds is 220 cm. Over this width there may be problems with equal closing of the strips.



A - system width
B - fabric width
chain A - B = 4,5 cm (2,3 + 2,2)
motor A - B = 5,0 cm (2,8 + 2,2)

Motors AC

Type	T [Nm]	rpm	wt [kg]	min. width	power supply	price
Torro AM35	6	28	21	55	0,49 A 230 V	67,2 EUR
Torro AM35Q	3	28	10	57	0,49 A 230 V	82,5 EUR
Torro AM35QMEL RF	3	28	10	57	0,38 A 230 V	120,0 EUR
Torro AM35QMEL RF	3	28	10	57	0,38 A 230 V	112,7 EUR
Somfy Sonesse 40	3	30	10	54	0,55 A 230 V	186,2 EUR
Somfy Sonesse 40 RTS	3	30	10	58	0,55 A 230 V	264,6 EUR
Somfy Screen Up	4,5	30	16	55	0,52 A 230 V	142,6 EUR

* Motor version without RJ plug.

Motors DC

Type	T [Nm]	rpm	wt [kg]	min. width	power supply	price
Torro AM35EB RF	6	18	21	85	1,5 A 16,8 V	155,2 EUR
Somfy Sonesse 30 RTS	2	28	9	46	0,8 A 24 V	244,2 EUR
Somfy Sonesse 30 WF RTS	2	28	9	69	1,5 A 12 V	236,4 EUR
Coulisse CM-03	1,1	28	4	55	1,8 A 5 V	147,3 EUR
Coulisse CM-05	2	28	7	73	2,9 A 5 V	198,7 EUR

* Power supply options - see „Additional accessories“.

** Motor not available in cassette version.

Versions

standard	Semi-cassette	Cassette	Ultimate
<p>Installation profile</p> <p>Roller blind is delivered with brackets attached to the installation profile. Installation profile is available only in colours (P).</p>	<p>Dimensions</p>	<p>Dimensions</p> <p>Roller blind is delivered in semi-cassette that partly covers tube with fabric. Semi-cassette is available only in colours (P). Version offered with surcharge.</p>	<p>Dimensions</p> <p>Roller blind is delivered in cassette that completely covers tube with fabric. Cassette is available only in colours (K). Version offered with surcharge.</p>
<p>Dimensions</p>	<p>Dimensions</p>	<p>Dimensions</p>	<p>Dimensions</p> <p>Roller blind is equipped with decoration valance and cheeks, made of stainless steel. Ultimate version is available only in colours (U). Version offered with surcharge.</p>

Brackets	Bottom bar	Loopless control
<p>installation profile</p> <p>semi-cassette cassette Ultimate</p>	<p>type D3 (standard) 457 g/m (alu.)</p> <p>type D4 767 g/m (alu.)</p>	<p>The roller blind movement is done by pulling on one of the two chains. This option is not available with the „Cassette“ version. Chain mechanism is available only in colours (P). Option offered with surcharge.</p>

Duo-Link	Multi-Link																																																					
<p>Total price is sum of two individual blinds. Option is not available with installation profile.</p>	<p>Boundary dimensions Multi-Link</p> <table border="1"> <thead> <tr> <th rowspan="2">Controls</th> <th colspan="4">fabric below 230 g/m²</th> <th colspan="4">fabric over 230 g/m²</th> </tr> <tr> <th colspan="2">2 blinds</th> <th colspan="2">3 blinds</th> <th colspan="2">2 blinds</th> <th colspan="2">3 blinds</th> </tr> <tr> <td></td> <td>MAX</td> <td>m²</td> <td>MAX</td> <td>m²</td> <td>MAX</td> <td>m²</td> <td>MAX</td> <td>m²</td> </tr> </thead> <tbody> <tr> <td>Chain</td> <td>560</td> <td>7,5</td> <td>580</td> <td>7,5</td> <td>560</td> <td>6,0</td> <td>580</td> <td>6,0</td> </tr> <tr> <td>Motor DC</td> <td>440</td> <td>10,0</td> <td>580</td> <td>18,0</td> <td>400</td> <td>8,0</td> <td>580</td> <td>7,0</td> </tr> <tr> <td>Motor AC</td> <td>560</td> <td>15,0</td> <td>580</td> <td>20,0</td> <td>560</td> <td>9,0</td> <td>580</td> <td>9,0</td> </tr> </tbody> </table> <p>Total price is the sum of prices of individual blinds. In Multi-Link the distance between fabrics is about 1,8 cm. When using system of height adjustment of roller blinds the distance between fabrics increases up to about 2,7 cm. Option is not available with installation profile.</p>	Controls	fabric below 230 g/m ²				fabric over 230 g/m ²				2 blinds		3 blinds		2 blinds		3 blinds			MAX	m ²	MAX	m ²	MAX	m ²	MAX	m ²	Chain	560	7,5	580	7,5	560	6,0	580	6,0	Motor DC	440	10,0	580	18,0	400	8,0	580	7,0	Motor AC	560	15,0	580	20,0	560	9,0	580	9,0
Controls	fabric below 230 g/m ²				fabric over 230 g/m ²																																																	
	2 blinds		3 blinds		2 blinds		3 blinds																																															
	MAX	m ²	MAX	m ²	MAX	m ²	MAX	m ²																																														
Chain	560	7,5	580	7,5	560	6,0	580	6,0																																														
Motor DC	440	10,0	580	18,0	400	8,0	580	7,0																																														
Motor AC	560	15,0	580	20,0	560	9,0	580	9,0																																														

* The possibility to produce roller blind with bigger dimensions is possible after consultation.